

# Desktop HDD

**Data Sheet** 

### The Power of One

- Seagate brings over 30 years of trusted performance and reliability to the new Seagate<sup>®</sup> Desktop HDDs—now available in capacities up to 4TB.
- Double your capacity and reduce costs with up to 1.25TB-per-disk hard drive technology.
- SATA 6Gb/s interface optimises burst performance.
- Seagate AcuTrac<sup>™</sup> servo technology delivers dependable performance.
- Free Seagate DiskWizard<sup>™</sup> software allows you to install 3TB and 4TB hard drives in Windows without UEFI BIOS.
- Seagate Secure<sup>™</sup> models provide hardware-based data security and deliver an Instant Secure Erase feature for safe, fast and easy drive retirement.<sup>1</sup>
- Seagate Secure models meet the NIST 800-88 media sanitisation specification and also support the Trusted Computer Group (TCG) Opal standard.<sup>1</sup>

#### **Best-fit Applications**

- Desktop or all-in-one PCs
- Home servers
- Entry-level direct-attached storage devices (DAS)

<sup>1</sup> Seagate Secure models are not available in all countries. May require TCG-compliant host or controller support.



## Desktop HDD

Seagate	•
---------	---

Specifications	4TB1	3TB1	2TB1	1TB <sup>1</sup>	500GB1	320GB1	250GB1
Standard Model Numbers	ST4000DM000	ST3000DM001	ST2000DM001	ST1000DM003	ST500DM002 <sup>2</sup>	ST320DM000 <sup>2</sup>	ST250DM000 <sup>2</sup>
Seagate Secure <sup>™</sup> Model Numbers		ST3000DM002	ST2000DM001	ST1000DM003	31300DW002	51520DW0000	51250010000
		formerly	formerly	formerly	formerly	formerly	formerly
Model Name	Desktop HDD	Barracuda®	Barracuda	Barracuda	Barracuda	Barracuda	Barracuda
Interface Options	SATA 6Gb/s NCQ	SATA 6Gb/s NCQ	SATA 6Gb/s NCQ	SATA 6Gb/s NCQ	SATA 6Gb/s NCQ	SATA 6Gb/s NCQ	SATA 6Gb/s NCQ
Performance							
Cache, Multi-segmented (MB)	64	64	64	64	16	16	16
SATA Transfer Rates Supported (Gb/s)	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5
Seek Average, Read (ms)	12	<8.5	<8.5	<8.5	<8.5	<8.5	<8.5
Seek Average, Write (ms)	12	<9.5	<9.5	<9.5	<9.5	<9.5	<9.5
Average Data Rate, Read/Write (MB/s)	146	156	156	156	125	125	125
Max Sustained Data Rate, OD Read (MB/s)	180	210	210	210	144	144	144
Configuration/Organisation							
Heads/Discs	8/4	6/3	4/2	2/1	2/1	2/1	1/1
Bytes per Sector	4,096	4,096	4,096	4,096	4,096 or 512 <sup>2</sup>	4,096 or 512 <sup>2</sup>	4,096 or 512 <sup>2</sup>
Voltage	1,000	1,000	1,000	1,000	1,000 01 012	1,000 01 012	1,000 01 012
Voltage Tolerance, Inc. Noise (5V)	±5%	±5%	±5%	±5%	±5%	±5%	±5%
Voltage Tolerance, Inc. Noise (12V)	±10%	+10%/-7.5%	+10%/-7.5%	+10%/-7.5%	+10%/-7.5%	+10%/-7.5%	+10%/-7.5%
Reliability/Data Integrity							
Contact Start/Stop Cycles	—	—			50,000	50,000	50,000
Load/Unload Cycles	300,000	300,000	300,000	300,000			—
Non-recoverable Read Errors per Bits Read, Max	1 per 1014	1 per 1014	1 per 1014	1 per 1014	1 per 1014	1 per 1014	1 per 1014
Workload Rate Limit (TB/year)	55	55	55	55	55	55	55
Power-on Hours	2,400	2,400	2,400	2,400	2,400	2,400	2,400
Limited Warranty (years) <sup>3</sup>	2	2	2	2	2	2	2
Power Management							
Startup Power (A)	2.0	2.5	2.5	2.0	2.0	2.0	2.0
Operating Mode, Typical (W)	5.6	8.0	8.0	5.90	6.19	6.19	6.19
Idle Average (W) <sup>4</sup>	4.0	5.4	5.4	3.6	4.60	4.60	4.60
Standby Mode (W)	0.50	0.75	0.75	0.63	0.79	0.79	0.79
Sleep Mode (W)	0.50	0.75	0.75	0.63	0.79	0.79	0.79
Environmental							
Temperature							
Operating (ambient min °C)	0	0	0	0	0	0	0
Operating (drive case max °C)	60	60	60	60	60	60	60
Non-operating (ambient °C)	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70
Halogen-free	Yes	Yes	Yes	Yes	Yes	Yes	Yes
RoHS compliance	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Physical							
Height (mm/in)	26.11/1.028	26.11/1.028	26.11/1.028	20.17/0.7825	19.98/0.787	19.98/0.787	19.98/0.787
Width (mm/in)	101.6/4.0	101.6/4.0	101.6/4.0	101.6/4.0	101.6/4.0	101.6/4.0	101.6/4.0
Depth (mm/in)	146.99/5.787	146.99/5.787	146.99/5.787	146.99/5.787	146.99/5.787	146.99/5.787	146.99/5.787
Weight (g/lb)	610/1.345	626/1.38	626/1.38	400/0.88	415/0.92	415/0.92	415/0.92
Carton Unit Quantity	20	20	20	20/255	25	25	25
Cartons per Pallet	40	40	40	40	40	40	40
Cartons per Layer	8	8	8	8	8	8	8
Special Features							
Seagate AcuTrac <sup>™</sup> Technology	Yes	Yes	Yes	Yes	No	No	No

<sup>1</sup> One gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes when referring to drive capacity.
<sup>2</sup> Seagate ships this drive in both 4K- and 512-byte sectors. SmartAlign technology is included on 4K sector drives. Both drives are functionally and physically equivalent.
<sup>3</sup> Extended warranty products available. Consult your distributor for details.
<sup>4</sup> Idle information may be based on Idle 1 or Idle 2 specifications. Consult the product manual for more information.
<sup>5</sup> Seagate Secure model is packaged at 20 units per carton. Standard model is packaged at 25 units per carton.

#### www.seagate.com

AMERICAS ASIA/PACIFIC EUROPE, MIDDLE EAST AND AFRICA Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, +1 408 658 1000 Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, +65 6485 3888 Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, +33 1 41 86 10 00

© 2014 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Actitace, Bareau of Industry and Security (for more information, visit www.bis.doc.gov), and may be controlled for export, import and use in other countries. Seagate rectinious to for a seagate rectinious to the seagate rectinious of the sea