

AOC Monitors LED monitor

70 Series 20" Class, 1600 x 900

E2070Swn

Slim Design with Eco-Friendly and User-Friendly Features

The e2070Swn offers great image quality at 1600 x 900 resolution, while providing features that benefits you. The 20-inch class monitor is EPEAT Silver and Energy Star certified, with AOC's eSaver software to set low-power configuration and iMenu software to access the user-friendly On Screen Display. Slim in design with extra narrow bezel while offering vibrant images with 20M:1 contrast ratio, the e2070Swn is also VESA 100mm Wall Mount compliant.

Key Features

- 19.5" viewable image with 16:9 aspect ratio
- Extra narrow bezel and slim design
- Black with Hairline Texture in the front and matte back cover
- VGA connectivity
- VESA 100mm wall mount compliant























Slim in Design

AOC's e2070Swn has a slim design and extra narrow bezel that is perfect for saving desktop space, while giving you the optimum 19.5" viewable image screen with 16:9 aspect ratio. The LED backlit monitor runs a maximum 1600 x 900 resolution.



Clear Visibility and Vibrant Images

With a 20,000,000:1 contrast ratio and 5 ms response time, the e2070Swn provides vibrant images and reveals darker image areas in greater depth. You can watch videos or play games without missing a beat.



User-Friendly and Eco-Friendly Features

The e2070Swn comes with a VGA connectivity. The VESA 100mm Wall Mount compliant feature allows you to have the monitor mounted on the wall with the appropriate mounting accessory. The e2070Swn is both EPEAT Silver and Energy Star certified with low-power consumption, and comes with AOC's eSaver and iMenu software for both eco-friendly and user-friendly configuration and navigation.

E2070Swn Specifications

Cabinet Color	Black with Hairline Texture in the front and matte in the back
Panel	TFT Active Matrix LCD, LED Backlight
	20" Class, 16:9 Aspect Ratio
	19.5" Diagonal Viewable Area
Pixel Pitch	0.271mm(H) x 0.262mm (V)
Display Area	433.9mm(H) x 236.3mm(V)
Brightness	200 cd/m² (typical)
DCR	20M:1
Response Time	5ms (typical)
Viewing Angle	Horizontal: 90 Degrees (CR>10)
Viewing Angle	Vertical: 50 Degrees (CR>10)
Scanning Frequency	Horizontal: 30KHz~83KHz
scanning Frequency	Vertical: 50Hz~76Hz
Optimal Resolution	
Recommended Resolution	1600x900x60Hz 1600x900@60Hz
Supported Resolutions	640x480@60/67/72/75Hz 720x400@70Hz
	800x600@56/60/72/75Hz 832x624@75Hz
	1024x768@60/70/75Hz 1280x1024@60/75Hz 1280x720@60Hz 1600x900@60Hz
	11/7//
Color Depth	16.7M
User Control	Auto/Power
User Control Input Signal	Auto/Power 1 x VGA
User Control Input Signal Adjustability	Auto/Power 1 x VGA Tilt: -3° to +10°
User Control Input Signal	Auto/Power 1 x VGA
User Control Input Signal Adjustability	Auto/Power 1 x VGA Tilt: -3° to +10°
User Control Input Signal Adjustability Power Source	Auto/Power 1 x VGA Tilt: -3° to +10° Universal 110V~240V AC, 50/60Hz
User Control Input Signal Adjustability Power Source Power Consumption	Auto/Power 1 x VGA Tilt: -3° to +10° Universal 110V~240V AC, 50/60Hz Power On: <18W, Standby: < 0.5W, DC off: <0.3W
User Control Input Signal Adjustability Power Source Power Consumption Regulations	Auto/Power 1 x VGA Tilt: -3° to +10° Universal 110V~240V AC, 50/60Hz Power On: <18W, Standby: < 0.5W, DC off: <0.3W
User Control Input Signal Adjustability Power Source Power Consumption	Auto/Power 1 x VGA Tilt: -3° to +10° Universal 110V~240V AC, 50/60Hz Power On: <18W, Standby: < 0.5W, DC off: <0.3W CE ,FCC, cCSAus, RoHS, EPA Energy Star®, EPEAT® Silver, Windows 8
User Control Input Signal Adjustability Power Source Power Consumption Regulations Special Features	Auto/Power 1 x VGA Tilt: -3° to +10° Universal 110V~240V AC, 50/60Hz Power On: <18W, Standby: < 0.5W, DC off: <0.3W CE ,FCC, cCSAus, RoHS, EPA Energy Star®, EPEAT® Silver, Windows 8 Extra narrow bezel, VESA 100mm x100mm Wall Mount Compliant ¹ ,
User Control Input Signal Adjustability Power Source Power Consumption Regulations	Auto/Power 1 x VGA Tilt: -3° to +10° Universal 110V~240V AC, 50/60Hz Power On: <18W, Standby: < 0.5W, DC off: <0.3W CE ,FCC, cCSAus, RoHS, EPA Energy Star®, EPEAT® Silver, Windows 8 Extra narrow bezel, VESA 100mm x100mm Wall Mount Compliant¹, Includes AOC's e-Saver, Screen+ and iMenu software
User Control Input Signal Adjustability Power Source Power Consumption Regulations Special Features Dimensions (WxHxD mm)	Auto/Power 1 x VGA Tilt: -3° to +10° Universal 110V~240V AC, 50/60Hz Power On: <18W, Standby: < 0.5W, DC off: <0.3W CE ,FCC, cCSAus, RoHS, EPA Energy Star®, EPEAT® Silver, Windows 8 Extra narrow bezel, VESA 100mm x100mm Wall Mount Compliant¹, Includes AOC's e-Saver, Screen+ and iMenu software Monitor (w/base): 465.0x346.4x156, Carton: 519x107x359
User Control Input Signal Adjustability Power Source Power Consumption Regulations Special Features Dimensions (WxHxD mm)	Auto/Power 1 x VGA Tilt: -3° to +10° Universal 110V~240V AC, 50/60Hz Power On: <18W, Standby: < 0.5W, DC off: <0.3W CE ,FCC, cCSAus, RoHS, EPA Energy Star®, EPEAT® Silver, Windows 8 Extra narrow bezel, VESA 100mm x100mm Wall Mount Compliant¹, Includes AOC's e-Saver, Screen+ and iMenu software Monitor (w/base): 465.0x346.4x156, Carton: 519x107x359 Monitor (w/ base): 18.3 x 13.6 x 6.1, Carton: 20.4 x 4.2 x14.1
User Control Input Signal Adjustability Power Source Power Consumption Regulations Special Features Dimensions (WxHxD mm) Dimensions (WxHxD inches)	Auto/Power 1 x VGA Tilt: -3° to +10° Universal 110V~240V AC, 50/60Hz Power On: <18W, Standby: < 0.5W, DC off: <0.3W CE ,FCC, cCSAus, RoHS, EPA Energy Star®, EPEAT® Silver, Windows 8 Extra narrow bezel, VESA 100mm x100mm Wall Mount Compliant¹, Includes AOC's e-Saver, Screen+ and iMenu software Monitor (w/base): 465.0x346.4x156, Carton: 519x107x359 Monitor (w/ base): 18.3 x 13.6 x 6.1, Carton: 20.4 x 4.2 x14.1 5.1 lbs Net, 2.3 kg
User Control Input Signal Adjustability Power Source Power Consumption Regulations Special Features Dimensions (WxHxD mm) Dimensions (WxHxD inches) Weight	Auto/Power 1 x VGA Tilt: -3° to +10° Universal 110V~240V AC, 50/60Hz Power On: <18W, Standby: < 0.5W, DC off: <0.3W CE ,FCC, cCSAus, RoHS, EPA Energy Star®, EPEAT® Silver, Windows 8 Extra narrow bezel, VESA 100mm x100mm Wall Mount Compliant¹, Includes AOC's e-Saver, Screen+ and iMenu software Monitor (w/base): 465.0x346.4x156, Carton: 519x107x359 Monitor (w/ base): 18.3 x 13.6 x 6.1, Carton: 20.4 x 4.2 x14.1 5.1 lbs Net, 2.3 kg 7.1 lbs Gross, 3.2 kg
User Control Input Signal Adjustability Power Source Power Consumption Regulations Special Features Dimensions (WxHxD mm) Dimensions (WxHxD inches) Weight Loading Qty w/pallet	Auto/Power 1 x VGA Tilt: -3° to +10° Universal 110V~240V AC, 50/60Hz Power On: <18W, Standby: < 0.5W, DC off: <0.3W CE ,FCC, cCSAus, RoHS, EPA Energy Star®, EPEAT® Silver, Windows 8 Extra narrow bezel, VESA 100mm x100mm Wall Mount Compliant¹, Includes AOC's e-Saver, Screen+ and iMenu software Monitor (w/base): 465.0x346.4x156, Carton: 519x107x359 Monitor (w/ base): 18.3 x 13.6 x 6.1, Carton: 20.4 x 4.2 x14.1 5.1 lbs Net, 2.3 kg 7.1 lbs Gross, 3.2 kg 20' = 1220 pcs; 40' Std = 2562 pcs
User Control Input Signal Adjustability Power Source Power Consumption Regulations Special Features Dimensions (WxHxD mm) Dimensions (WxHxD inches) Weight Loading Qty w/pallet	Auto/Power 1 x VGA Tilt: -3° to +10° Universal 110V~240V AC, 50/60Hz Power On: <18W, Standby: < 0.5W, DC off: <0.3W CE,FCC, cCSAus, RoHS, EPA Energy Star®, EPEAT® Silver, Windows 8 Extra narrow bezel, VESA 100mm x100mm Wall Mount Compliant¹, Includes AOC's e-Saver, Screen+ and iMenu software Monitor (w/base): 465.0x346.4x156, Carton: 519x107x359 Monitor (w/ base): 18.3 x 13.6 x 6.1, Carton: 20.4 x 4.2 x14.1 5.1 lbs Net, 2.3 kg 7.1 lbs Gross, 3.2 kg 20' = 1220 pcs; 40' Std = 2562 pcs 685417056583

^{1.} Wall mount arm & bracket are not included.

Actual product may vary from image shown on datasheet. The information contained herein is subject to change without notice. AOC shall not be liable for technical or editorial errors or omissions contained herein. All other trademarks are property of their respective owners.

For more information, visit us.aoc.om or Call 888-838-6388